



SAFETY WORK PLATFORMS

"Star Attachments Turn a Forklift into a Whole Fleet of Equipment"



Model 1208G

**Meets / Exceeds
OSHA & ANSI
Requirements**

- ▶ GOES WHERE SCISSOR-LIFTS CAN'T
- ▶ FASTER THAN SCAFFOLD
- ▶ PROVIDES A WIDER PLATFORM THAN BOOM LIFTS
- ▶ REACHES OVER OBSTRUCTIONS
- ▶ SIMPLE AND INEXPENSIVE

SAFETY WORK PLATFORMS TURN YOUR FORKLIFT INTO AN AERIAL WORK PLATFORM

NEW IMPROVED ENTRANCE GATE DESIGN & MODULAR COMPONENT GUARDRAILS

- ❶ Spring Hinges and Spring Loaded Latches provides Self-Closing and Latching Gate Action - Increased Safety.
- ❷ New Modular Component Guardrails - Stronger and more rigid - no more loose movement in the rail system. Component Design also allows for replacement of individual components in lieu of having to replace a complete guardrail panel should damage occur.

Other Features ▶

- Expanded Metal Deck
- 1½" sq. tube Guardrails
- 1" dia. Fork Retaining Pins w/ pin storage
- End Fork Loops for easier handling of platform
- Integral 5½" high Toeboards



Goes Where Scissor-Lifts Can't

**Quick-Tach
&
Slip-on-Forks**
Models Available



Faster Than Scaffold

800-541-1797


or

817-485-6073

Safety Work Platforms for forklifts

CHOOSE FROM 2 STYLES

Both are Quick & Easy to Install



"Slip-On-Forks"




...OR

"Quick-Tach"

Forklift must be equipped with a "quick-tach".

Self-Closing Access Gate at each end



Forklift Attachments

Specifications

- ▶ **Full Perimeter Guard Rail System** constructed of 1½" square steel tubing & consisting of a 42" high top rail, a mid rail, and 5½" high intregel toeboards. Access gates with spring hinges and spring loaded latches provide self-closing and latching gate action for added safety are provided at each end. The modular component design allows for easy replacement of individual components. Entire Guard Rail System can be easily removed and laid flat inside platform for transportation.
- ▶ **Deck** consists of a strong but lightweight engineered steel frame with expanded metal deck.
- ▶ The **"Universal Fit" Slip-On-the-Forks** design can be used with both Extendible Reach and Straight Mast forklifts. Forks slide into steel fork pockets and are secured with two heavy duty steel pins behind the heel of the forks. They are designed for use with a 48" or wider carriage and 48" long forks up to 7" wide and 2¾" thick. Forks longer than 48" can be used, however, they will extend out past the front of the platform.
- ▶ The **Quick-Tach** models are built to fit specific makes & models of forklifts that are equipped with a quick-tach. The forks and carriage are removed and the Platform attaches to the boom.
- ▶ **All Models are rated at 1,000 lbs. load capacity.** Rating applies to platform only and does not reflect capacity of forklift.
- ▶ **Optional Mast Protection Screen** (Model 1250) protects personnel from moving parts of forklift mast. Constructed of square steel tubing and expanded metal, the screen measures 42" wide x 84" tall. It attaches to the back guardrail with u-bolts. A mast protection screen should be used with all straight mast forklifts and with any others where a mast poses a safety hazard.



UNIVERSAL FIT "Slip-on-Forks" MODELS		
Model	Size	Weight
1204C	4' x 4'	xxx lbs.
1206C	4' x 6'	xxx lbs.
1208C	4' x 8'	440 lbs.
1210C	4' x 9' 8"	520 lbs.

When ordering for use on a Genie or Terex, use the suffix "G" instead of C.


"QUICK-TACH" MODELS		
Model	Size	Weight
1204C QT	4' x 4'	± xxx lbs.
1206C QT	4' x 6'	± xxx lbs.
1208C QT	4' x 8'	± 590 lbs.
1210C QT	4' x 9' 8"	± 670 lbs.

Specify forklift make & model when ordering QT platforms.

SPECIAL SAFETY NOTE:

I.T.S.D.F. Standard B56.6 for Rough Terrain Forklift Trucks states that ... the platform floor dimension shall not exceed the overall width of the truck (measured across the load bearing tires) plus 10" on either side. Star Industries recommends that all users of Star Safety Work Platforms conform to this requirement as well as the other requirements of B56.6. Furthermore, users should conform to all applicable local, state, and federal safety standards. Star Industries recommends you contact the respective forklift manufacturer for any additional safety requirements or limitations.

Fork Pocket Size: 48" long x 7¾" x 3" ID / Center to Center of Fork Pockets: 38" / Pocket Ends are open.



4101 Garland Dr., Fort Worth, TX 76117
 Ph 817-485-6073 Fax 817-428-6008
USA & Canada Toll Free 800-541-1797
www.starindustries.com

Operating Manual/Safety Information
 Available online - www.starindustries.com